



US009636940B2

(12) **United States Patent**  
**Kamitani et al.**

(10) **Patent No.:** **US 9,636,940 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **WRITING INSTRUMENT**

(71) Applicant: **MITSUBISHI PENCIL COMPANY, LIMITED**, Shinagawa-ku, Tokyo (JP)

(72) Inventors: **Toshimi Kamitani**, Yokohama (JP);  
**Satoru Banzai**, Fujioka (JP);  
**Yoshiharu Namiki**, Yokohama (JP);  
**Yosuke Setagawa**, Fujioka (JP);  
**Hitoshi Kino**, Fujioka (JP); **Tooru Nakajima**, Yokohama (JP); **Takanori Suzuki**, Fujioka (JP)

(73) Assignee: **MITSUBISHI PENCIL COMPANY, LIMITED**, Tokyo (JP)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 43 days.

(21) Appl. No.: **14/647,925**

(22) PCT Filed: **Dec. 3, 2013**

(86) PCT No.: **PCT/JP2013/082442**

§ 371 (c)(1),

(2) Date: **May 28, 2015**

(87) PCT Pub. No.: **WO2014/087988**

PCT Pub. Date: **Jun. 12, 2014**

(65) **Prior Publication Data**

US 2015/0298489 A1 Oct. 22, 2015

(30) **Foreign Application Priority Data**

Dec. 4, 2012 (JP) ..... 2012-265158

Dec. 4, 2012 (JP) ..... 2012-265159

(Continued)

(51) **Int. Cl.**

**B43K 7/08** (2006.01)

**B43K 23/12** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **B43K 23/12** (2013.01); **B43K 5/18** (2013.01); **B43K 7/01** (2013.01); **B43K 7/02** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC ..... **B43K 23/123**; **B43K 8/026**; **B43K 8/03**; **B43K 8/06**

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,474,895 B2 \* 11/2002 Hori ..... **B43K 5/18** 401/205

FOREIGN PATENT DOCUMENTS

GB 722448 A 1/1955  
JP 6-71172 U 10/1994

(Continued)

OTHER PUBLICATIONS

International Preliminary Report and Written Opinion issued on Jun. 18, 2015, by the International Bureau in corresponding International Application No. PCT/JP2013/082442 (9 pages).

(Continued)

*Primary Examiner* — Jennifer C Chiang

(74) *Attorney, Agent, or Firm* — Buchanan, Ingersoll & Rooney PC

(57) **ABSTRACT**

Provided is a writing instrument suited to ballpoint pens, marking pens and the like in which a flow pressure of an ink applied to a pen tip is controlled to a fixed level to prevent an ink direct flow phenomenon reverse flow phenomenon. The above writing instrument comprises a pen tip disposed at a front part of an ink tank, an ink received in the ink tank, a follower filled at a rear part of the ink, and a capillary porous member provided with a capillary force, which is arranged at a space part between a rear part of the follower

(Continued)

